

ProLite E2773HDS


The LED-backlit ProLite E2773HDS 27" LCD Display features a stunning 1 ms Response Time and a High Definition 1920 x 1080 Resolution. The 5 000,000:1 Advanced Contrast Ratio and 300 cd/m² brightness offer the user clear and vivid images, and the HDMI, DVI and D-Sub connections ensure compatibility across a range of devices including games consoles and work stations. The display is Windows® 7 Compatible and Energy Star® 5.0 qualified.

DISPLAY CHARACTERISTICS

Diagonal	27"
Panel	TN
Display area h x w	336.3 x 597.9 mm; 13.2" x 23.5"
Response time	1 ms
Contrast	1200 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.311 x 0.311 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	28 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

DIMENSIONS / WEIGHT

Dimensions w x h x d	647 x 454.5 x 239 mm
Weight	5.3 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	D-Sub
Digital input connector	DVI-D, HDMI
HDCP	yes
Output connector	headphone socket

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2B™
Controls	Via OSD in 8 languages (EN, DE, FR, ES, IT, FIN, Chinese, JP) and 5 front controls (Power, Select/ Input Select, Scroll up/ Audio , Scroll down/ i-Style Colour, Menu)
User controls	auto adjust, contrast/brightness (contrast, brightness, ACR, ECO, OD), input select, audio adjust (volume, mute, HDMI audio), colour adjust, information, manual image adjust (clock, H/V position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, LED), memory recall
Speakers	2 x 2 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Ergonomics	CE, ENERGY STAR®
Safety	TÜV-Bauart, PSE, CB, GOST-R, VCCI-B
Tilt angle	20° up; ° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista/ 7
Included accessories	power cable, D-Sub cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide